



Trex® Technical Bulletin:
CANADA ADDENDUM TO INSTALLATION INSTRUCTIONS –
CCMC REQUIREMENTS ONLY

Document No: TTB-0040

Rev: -

Date: 5/6/24

For Trex Transcend and Select Decking, the following changes are to be followed with respect to spans and gapping instructions; these spans are specific for CCMC requirements only.

Canada Allowable Joist and Stair Stringer Spacing:

<i>Product</i>	<i>Maximum Allowable Joist Spacing</i>	<i>Maximum Allowable Stair Stringer Spacing</i>
21mm x 140 mm Select Decking	400 mm	200 mm
24mm x 140 mm Transcend Decking	400 mm	230 mm
33mm x 140 mm Select Decking	600 mm	250 mm
33mm x 140 mm Transcend Decking	600 mm	250 mm

Canada Gapping Requirements:

<i>Gap Type</i>	<i>Temperature at time of Installation</i>	<i>Minimum Gap Requirement (mm)</i>
Width to Width gap	Above -9 °C	5
End to End	Above 15°C	4
End to End	Between 3 °C to 15 °C	6
End to End	Between -9 °C to 3 °C	8
End to Solid Object	Above 3 °C	6
End to Solid Object	Between -9 °C to 3 °C	13